

LXR08 Design: Gino Carollo, 2020



Technical details

Model

Inner frame Inner frame seat

Solid beech, and sheet material
Hard steel zig-zag springs

Wadding

HR foam 50kg/m³, wadding: Leoskin
HR foam 30kg/m³, wadding: Leoskin
Polyether foam 20kg/m³, wadding: Leoskin

Legs

Aluminium polished or all standard epoxy colours (powder coating)

Gliders

Synthetic, black

Note

At the arm and backside, the legs go into the wings of the sofa. In other positions, the legs are positioned under the seat. The elements 600 and 650 have no front legs. The corner elements 600 and 650 cannot be connected to the chaise longue 801-802-851-852.

Fold formation

Because of the loose appearance, small folds are part of the characteristic.

Upholstery

Fabric or leather
We do not recommend upholstery in patterned fabrics due to design and seam format.

Decorative stitching

Double-stitched decorative stitching and a flat seam.

Functions

Seat height Seat depth

Seat height +2cm
Seat depth -2cm (only available for sofas)

Comments

Certifications

All sheet materials used in this model comply with the CARB2 requirement or are NAF certified

All materials used in the furniture meet the legal requirements of the country of destination. Foam materials with flame-retardant characteristics can be supplied on request.

