leolux LX

LXR11 Design: Yonoh, 2020





Technical details

Model

Inner frame Solid beech and sheet material.

Inner frame footstool Sheet material.

Springs seat Hard steel zig zag springs.

Filling HR foam 50kg/m³, covering Leoskin.

HR foam 40kg/m³, covering Leoskin. HR foam 30kg/m³, covering Leoskin. Polyether foam 16kg/m³, covering Leoskin.

Legs Polished aluminium.

Option: All selected Epoxy colours (powder coating).

Gliders Black synthetic.

Decorative stitching Double-stitched decorative stitching.

Piping Piping follows the selected upholstery for the frame. On request a contrast

piping can be selected in leather or fabric. Contrast piping is only possible in

standard materials.

The elements in velours fabrics and leather have extra vertical seams on the rear

of the back.

Customize option Seat height + 2 cm.

Stitching The versions in leather have different seams, versions in vertically processed

fabrics follow the seams of the leather versions.

Special features Stretch fabrics cannot be combined with other upholstery materials. However, it

is possible to combine colours from the same stretch fabric.

Please note One of the seams on the back of the sofas, loveseats and connection sofas has

a hidden zipper. In a light upholstery material, the zipper can be visible as a thin

black stripe. (applicable for Versions 100, 300, 400, 500, 701 and 702).

Technical details

leolux LX

Comments

All sheet materials used in this model comply with the CARB2 requirement or are NAF certified.

Certifications

All materials used in the furniture meet the legal requirements of the country of destination. Foam materials with flame-retardant characteristics can be supplied on request.

leolux LX

