leolux LX

LXR01 Flint



DIMENSIONS

All witdth dimensions are rounded up. All dimensions are approximate.

TECHNICAL DATA

Inner frame	Solid beech and sheet material.
Springs seat	Hard steel zig zag springs.
Filling	HR foam 50kg/m³, covering Leoskin.
	HR foam 30kg/m³, covering Leoskin.
	Polyether foam 20kg/m³, covering Leoskin.
Legs Fino	Polished aluminium.
-	Option: All selected Epoxy colours (powder coating).
Legs Titan	Black Nickel
-	Option: All selected Epoxy colours (powder coating).
Gliders	Black synthetic.
Decorative stitching	Double-stitched decorative stitching and a flat seam.
Stitching	The elements in leather and velours fabrics have a different seam layout.
Customize option	Seat height +2cm via the legs.
	Seat depth -2cm via amended seat (not available for alle items).
Upholstery	We don't recommend patterned fabrics due to design.
	Not available in Stretch fabrics.
Please note	Connection and end elements have one connection-side. Therefore they cannot be used as
	freestanding elements and should always be connected.
Certifications	All sheet materials used in this model comply with the CARB2 requirement or are NAF certified.
	All materials used in the furniture meet the legal requirements of the country of destination.
	Foam materials with flame-retardant characteristics can be supplied on request.
Design	Beck Design, 2019.
Comfort options	
Comort options	