

leolux LX

LX396 Design: Braun and Maniatis, 2008



Technical details

Model

Inner frame seat Solid beech and plate material
Inner frame back Solid beech
Springs Hard steel zig-zag springs

Wadding HR foam 50kg/m³, wadding Leoskin
HR foam 25m³, wadding Leoskin
Polyether foam 75kg/m³, wadding Leoskin
Polyether foam 43kg/m³, wadding Leoskin

Upholstery

Upholstery Inner frame Only available in horizontal processed fabrics (no velvets).
Upholstery Fabric or leather
Stitching Colour-to-colour or one of the standard colours.

Legs

Legs Aluminium polished or synthetic black legs
Gliders Synthetic black

Functions

Seat height +1,5cm or +3cm (Synthetic black legs excluded)

Adjustable arm and / or back sections Standard locked, optionally pivoting backs. Pivot mechanism is provided with a gas spring. This can be unlocked / locked by pressing on the top of the back.

Comments

Pivot mechanisms The backs can be turned in four positions (each 90°). As a result, many combinations are possible with a limited number of elements.

The 3-seater elements have two backs with pivot points on the outside, 2x left or 2x right.

Technical details

leolux LX

Fabric width	For fabrics with a width of 130 cm, the seam is on the back of the top of the seat instead of on the back.
Mechanics	Do not use the swing backs as a seat
Certifications	All sheet materials used in this model comply with the CARB2 requirement or are NAF certified On request foam materials with additional flame retardants can be applied.

